

LGE 400 Edge Carry Lift Gate

Module: LGE-400 Edge Carry Lift Gate Conveyor
Length: 60" (1524mm)
Frame Style: Welded base frame with extruded aluminum and painted panels
Description: Provides a 37" (940mm) walkway on an "as needed" basis through the production line and is normally closed, operating as a transfer conveyor. Manually Raised.

Standard Features:

- **Programmable Logic Controller**
- Variable speed (10-45 fpm) (3 – 13.7mpm)
- **Easy-lift pivot gate design** with buffers to cushion closing action
- Operator controls (E-Stop, Reset, Release, Request)
- Switch selectable **buffering/non-buffering mode**
- **"Hand crank" width adjusting**
- "Look up" product sensor
- **Left to right travel, front rail fixed**
- ESD safe
- Painted sheet metal panels, "Dynapace White"
- Conforms to **SMEMA Spec. 1.2** and NFPA 79
- Includes 1 standard communication cable

Product Handling Capability:

Edge Clearance: 0.187" (4.87mm)
Length: 3" – 20" (76mm - 508mm)
Width: 3.5" – 18" (88.9mm - 457mm)
Thickness: 0.045" (1mm) minimum
Weight: Up to 5lbs (2.7kg) per foot
Above board clearance: N/A
Below board clearance: 0.5" (13mm)



Facilities Requirements:

Electrical: 115 VAC/15 amp
Air: N/A
Line height: 37" +/- 2" (940mm +/- 25mm)
Footprint: 60" L x 39" W x (1524mm L x 991mm W)